



**Part Number:**

55913882X X 00

- Series Number: .
- Original Number: .
- Number of contact: .
- No. of port: .
- Insulator Code:
  - 1-Black, 2-Gray
  - 3-White, 4-Beige
- Plating code:
  - 1-Gold flash plated over Nickel
  - 3-3u" Gold plated over Nickel
  - 5-5u" Gold plated over Nickel
  - 6-10u" Gold plated over Nickel
  - 7-15u" Gold plated over Nickel
  - 8-30u" Gold plated over Nickel

**Electrical:**  
 Current Rating : 1.5 Amp  
 Voltage Rating : 125 V  
 Dielectric Withstanding: 1000 VAC for one minute  
 Contact Resistance: < 30 mΩ  
 Insulation Resistance: > 500 MΩ  
 Operating Temperature: -40°C ~ +70°C  
 Material :  
 Housing :PBT(The Post & Board Lock Will Be Melting).  
 Contact: Phosphor Bronze.  
**Mechanical:**  
 Durability: 750 cycles min.  
 Insertion Force : 2.5KG.F max.  
 Retention Strength : 7.7KG.F min between jack and plug

E	Units	mm	Scale	3:1	Drawing By	Date			LEYCONN ELECTRONICS CO.,LTD.
D	Tolerance Unless Otherwise Specified				Kirby-Xiao	2013/06/01	<a href="http://www.leyconn.com">Http://www.leyconn.com</a>		LEYCONN ELECTRONICS CO.,LTD.
C	.X ~ ±0.30				Reviewed By	Date			深圳市联益康电子有限公司
B	.XX ~ ±0.25				Luli-Liu	2013/06/01			TEL: +86(755)26078616 FAX: 26070522
A	.XXX ~ ±0.20				Approval By	Date			55913 (5921S) 8P8C 2*1 RA Type
REV	DESCRIPTION.	Angle	~ ± 3°		Darren-Zhang	2013/06/01			55913882XX00

