This document contains information confidential and proprietary to LEYCONN and shall not be reproduced or transferred to another document or disclosed to others or used for any purpose other than that for which it was obtained without the express written consent of LEYCONN.

RoHS









RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW



NOTES:

SPECIFICATIONS:

Operation force: 1000gf Max
Operation temperature:-25°C to +70°C
Storage temperature :-40°C to +85°C
Mechaical Lire:3000cycles minimum

PLATING

GOLD FLASH 1u''(min) SOLDERTALL
3u'' GOLD PLATING ON THE CONTACT AREA
WITH 50u'' nickel underplatingoverall

ISSUED
leyconn
CONFIDENTIAL
2019-03-15

Construction



Number	Part Name	Material	Finished
①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movadie	Copper Alloy	3u"Gold
④	Terminal	Bross	1u"Gold
⑤	Base	UL94 V0	Black
⑥	TerminalContact	Bross	3u"Gold

Part Number:

460 NN 1 1 3 X 2 1 X

- Series Number: 460
- Number Contact: NN — 02-12
- Tial & Mounting Style: 1 — 1-Slide Type
- Pitch:(Unit:mm) 1 — 1-2.54
- Insulator: 3 — 3-Black
- Contact Plated: X — 0-Tin 1-Gold flash
- Packaging Options: 2 — 1-Tube Packaging
- Others: 1 — X

REV	DESCRIPTION.	Date
E		
D		
C		
B		
A	RELEASED	15/03/19

Units	mm	Scale	2:1
Tolerance Unless Otherwise Specified			
.X ~ ±0.30			
.XX ~ ±0.25			
.XXX ~ ±0.20			
Angle ~ ± 3°			

Drawing By	YP-Liang	Date 2019/03/15
Reviwed By	Nick-Yin	Date 2019/03/15
Approval By	Kirby-Xiao	Date 2019/03/15

Leyconn
Http://www.leyconn.com

LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司
TEL: +86(755)26078616 FAX: 26070522

Sheet 1 of 1
Third Angle Projection

Title	Switches Straight DIP Type H3.0
Part No.	460NN113X21X
REV	A