This document contains information confidential and proprietary to LEYCONN and shall not be reproduced or transferred to another document or disclosed to others or used for any purpose other than that for which it was obtained without the express written consent of LEYCONN.

RoHS



ISSUED
Leyconn
CONFIDENTIAL
2019-01-23

SPECIFICATIONS

Current Rating: 3 Amps
Withstanding Voltage: AC 600V/minute.
Insulation Resistance:1000MΩ Min
Contact Resistance: 20mΩ Max
Insulator Material: Polyester(UL94V-0) See Part Number
Contact Material: Phosphor bronze
Contact Plating: Au or Sn over 50u" Ni
Operation Temperature: -40°C to +105°C



RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW



With location



Without location

Part Number:

2 1 5 2 NN 3 X X X X 0

- Pitch: 1-2.54mm
- Height of Insulator: 5- 5.00mm
- Number of row: 2-Double row
- Pin number of each row: 01 ~40PIN
- Type of terminations : 3-Surface mount-perpendicular
- Insulator Material : 2-LCP 4-PA46 5-PA6T 9-PA9T
- Plating Code : 0-Tin over nickel; 1-Gold flash over nickel; 3-0.075um gold over nickel; 5-0.125um gold over nickel; 6-0.25um gold over nickel; 7-0.375um gold over nickel; 8-0.75um gold over nickel
- Location Peg ,Pick &place pad Options: 0-Without Location 1-With Location 2-With CAP 3-With CAP +Location 4-Without Location + Mylar
- Packaging Options : 1-Tube Packaging 2-Tape & Reel Packaging 3-Pallet Packaging

REV	DESCRIPTION.	Date
E		
D		
C		
B		
A	RELEASED	23/01/19

Units mm | Scale 3:1

Tolerance Unless Otherwise Specified
.X ~ ±0.30
.XX ~ ±0.25
.XXX ~ ±0.20
Angle ~ ± 3°

Drawing By	Lin-Wu	Date 2019/01/23
Reviwed By	YP-Liang	Date 2019/01/23
Approval By	Kirby-Xiao	Date 2019/01/23

Leyconn
Http://www.leyconn.com

LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司
TEL: +86(755)26078616 FAX: 26070522

Sheet 1 of 1
Third Angle Projection

Title: 2.54mm Female Header, Straight S.M.T Type, H=5.0mm
Part No. 2152NN3XXXX0 REV A