


Electrical Data:
Current rating: 1A
Dielectric Withstanding Voltage: 1000V AC for one minute
Contact Resistance: < 20 mΩ
Insulation Resistance: > 1000 MΩ
Operating Temperature: -40°C ~ +105°C

Construction:
Insulator: Black Glass Filled Polyester
Flammability Rating: UL 94V-0
Contacts: Brass
Contacts plating: Gold or Tin over nickel
SQ Pin :0.40*7.80

Part Number:

393 NN 0 3 X X X 00

- Pitch:(Unit:mm)
3-1.27x1.27
- Number of Contact:
10 ~ 64 PIN
- Type of terminations:
3 - SMT Type
- Insulator Color:
1-Black
- Insulator Material:
2-LCP
5-PA6T
9-PA9T
- Contact Plated:
0-Tin
3-Gold 3u"
6-Gold 10u"
8-Gold 30u"
- 1-Gold Flash
5-Gold 5u"
7-Gold 15u"



E					Units	mm	Scale	2:1	Drawing By	Date	<div>LEYCONN ELECTRONICS CO.,LTD. 深圳市联益康电子有限公司 TEL: +86(755)26078616 FAX: 26070522</div>			
D					Tolerance Unless Otherwise Specified				yp-Liang	2019/04/03	Http://www.leyconn.com			
C									Revised By	Date	Sheet		1 of 1	
B					.X ~ ±0.30				Loek-Wu	2019/04/03	Third Angle Projection		Title	
A					.XX ~ ±0.25				Approval By	Date	Part No.		Elector Header Connector Pitch:1.27mm SMT Type W5.60 H11.40	
REV					.XXX ~ ±0.20				Kirby-Xiao	2019/04/03			Pitch:1.27mm SMT Type W5.60 H11.40	
					Angle ~ ± 3°								REV A	
1	2	3	4	5	6	7	8							