







RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW

Specifications:

1. Material:

Insulator : LCP (black) UL94V-0

Terminal : Phosphor bronze or brass.

Peg : brass

2. Operating temperature : -55°C ~ +125°C

3. Rating current : 1.0A AC/DC

4. Contact resistance : < 20mΩ

5. Withstand voltage : 500V AC for one minute

6. Insulation resistance : > 100MΩ

7. Finish:

Terminal : Gold/Tin plating on contact area

100u"min. Tin-Lead Plating on solder tails

50u"min. Nickel under plating over all

Peg : 100u"min. Tin-Lead Plating on solder tails

50u"min. Nickel under plating over all

Part Number:

470 22 2 1 0 X 1 0 X

Product Series

470

Number of Contacts:-

22 - 7+15 PIN

Tail Style:

2-Right Angel Solder

Locating peg option:-

1-with locating peg

Type of terminations:-

0 - Standard

Insulator Code:

1-Black

Plating Code :

1-Selective gold flash over nickel

3-Selective 0.075um gold over nickel

5-Selective 0.125um gold over nickel

6-Selective 0.25um gold over nickel

7-Selective 0.375um gold over nickel

8-Selective 0.75um gold over nickel



leyconn

LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司
TEL: +86(755)26078616 FAX: 26070522

Lin-Wu

Date

2019/04/29

Reviewed By

Date

2019/04/29

YP-Liang

Date

2019/04/29

Approval By

Date

2019/04/29

Kirby-Xiao

Date

2019/04/29

Http://www.leyconn.com

SATA 7+15母座 RA 沉板型

Sheet

1 of 1

Third Angle Projection

Part No.

47022210X10X

REV

A