



This document contains information confidential and proprietary to LEYCONN and shall not be reproduced or transferred to another document or disclosed to others or used for any purpose other than that for which it was obtained without the express written consent of LEYCONN.

RoHS









RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW

SPECIFICATIONS
Current Rating: 1A
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Withstand Voltage:300V AC/minute
Operation Temperature:-40℃ to +105℃
Contact Material: Brass
Contact Plating:Au or Sn over 50μ"Ni
Insulator Material:Polyester(UL94V-0)
SQ PIN : 0.46 X D+A+(W-2.54)/2-0.40mm

N=No. of contacts / per row

Dim \ P位	(1-49)	50
Dim A	1.27*N-0.20	63.5
Dim B	1.27*(N-1)	

ISSUED
Leyconn
CONFIDENTIAL
2019-02-26

Part Number:

34 2 NN X X 3 XXX X

Pitch(Unit:mm):
4-1.27 * 2.54
Number of Row:
2-Double Row
Pin number of each row:
01 ~ 50 PIN
Insulator Material:
2-LCP 4-PA46 5-PA6T 9-PA9T
Contact Plated:
0-Tin over nickel ,1-Gold flash over nickel
2 -0.05um gold over nickel 3-0.075um gold over nickel,
5-0.125um gold over nickel 6-0.25um gold over nickel,
7-0.375um gold over nickel 8-0.75um gold over nickel,
A-0.02um gold over nickel B-0.01um gold over nickel
Tail & Mounting Style:
3-Surface mount perpendicular
Pin Length:
XXX~A+D+(W-1.27)/2-0.40
Serial number:
Determined by the LEYCONN

REV	DESCRIPTION.	Date
E		
D		
C		
B		
A	RELEASED	26/02/19

Units: mm | Scale: 4:1

Tolerance Unless Otherwise Specified
.X ~ ±0.30
.XX ~ ±0.25
.XXX ~ ±0.20
Angle ~ ± 3°

Drawing By	Hui-Wen	2019/02/26
Reviwed By	Nick-Yin	2019/02/26
Approval By	Kirby-Xiao	2019/02/26

Leyconn
Http://www.leyconn.com
LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司
TEL: +86(755)26078616 FAX: 26070522

Sheet 1 of 1
Third Angle Projection

Title	1.27*2.54mm PIN Header S.M.T Type
Part No.	342NNXX3XXXX
REV	A