This document contains information confidential and proprietary to LEYCONN and shall not be reproduced or transferred to another document or disclosed to others or used for any purpose other than that for which it was obtained without the express written consent of LEYCONN.

RoHS









ISSUED
Leyconn
CONFIDENTIAL
2018-07-19

Electrical Data-

Current rating: 2Amps
Dieltric Withstanding Voltage: 1000VAC for one minute
Contact Resistance: < 30 Milliohms
Insulation Resistance: > 1000 Megaohms min. at DC 500V.
Operating Temperature: -55°C ~ +105°C

Construction:

Insulator: 30% Glass Filled PBT
Flammalility Rating: UL 94V-0
Contacts: Brass

Part Number:

416 3 48 1 1 1 X X X

Contact Number of Row:
3- a + b + c row

Number of Contact:
48 PIN

Contact Type:
1-Male

Type ofterminations:
1-Straight solder

Pitch:
1-2.54mm

Others:

Solder Length:
0-3.00mm 1-4.00mm
2-2.50mm 3-13.00mm
4-17.00mm 5-4.50mm

Contacts Plating:
1-Gold Flash
3-Gold 3u"
5-Gold 5u"
6-Gold 10u"
7-Gold 15u"
8-Gold 30u"

REV	DESCRIPTION.	Date
E		
D		
C		
B		
A	RELEASED	19/07/18

Units: mm | Scale: 1:1

Tolerance Unless Otherwise Specified
.X ~ ±0.30
.XX ~ ±0.25
.XXX ~ ±0.20
Angle ~ ± 3°

Drawing By	Hui-Wen	Date 2018/07/19
Reviwed By	Nick-Yin	Date 2018/07/19
Approval By	Kirby-Xiao	Date 2018/07/19

Leyconn
Http://www.leyconn.com

LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司
TEL: +86(755)26078616 FAX: 26070522

Sheet 1 of 1
Third Angle Projection

Title: DIN 41612 348公直系列
Part No.: 416348111XXX
REV: A