



Electrical Data-
Current rating: 2Amps
Dielectric Withstanding Voltage: 1000VAC for one minute
Contact Resistance: < 30 Milliohms
Insulation Resistance: > 1000 Megaohms min. at DC 500V.
Operating Temperature: -65°C ~ +105°C

Construction:
Insulator: 30% Glass Filled PBT
Flammability Rating: UL 94V-0
Contacts: Phosphor Bronze

Part Number:

416 2 64 2 1 1 XXX

Contact Number of Row: 2- a + b row

Number of Contact: 64 PIN

Contact Type: 2-Female

Type of terminations: 1-Straight solder

Pitch: 1-2.54mm

Others:

Solder Length:

- 0-3.00mm
- 1-4.00mm
- 2-2.50mm
- 3-13.00mm
- 4-17.00mm
- 5-4.50mm

Contacts Plating:

- 1-Gold Flash
- 3-Gold 3u"
- 5-Gold 5u"
- 6-Gold 10u"
- 7-Gold 15u"
- 8-Gold 30u"

leyconn

Http://www.leyconn.com

LEYCONN ELECTRONICS CO.,LTD.
深圳市联益康电子有限公司

TEL: +86(755)26078616 FAX: 26070522

Sheet 1 of 1

Title

DIN 41612 264母直系列

Third Angle Projection

Part No.

416264211XXX

REV A

E		Units	mm	Scale	1:1	Drawing By	Date
D		Tolerance Unless				Lin-Wu	2019/02/14
C		Otherwise Specified				Reviewed By	Date
B		.X ~ ±0.30				YP-Liang	2019/02/14
A		.XX ~ ±0.25				Approval By	Date
REV	DESCRIPTION.	.XXX ~ ±0.20	Angle	~ ± 3°		Kirby-Xiao	2019/02/14