





Technical Specs:

Insulator: Black glass filled polyester PBT-GF30-FR
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3 (C36000)
 Mechanical life: min 500 cycles
 Rated current: 3 A
 Contact resistance: max 20 Milliohms
 Dielectric strength: min 1000 V RMS



151-XXX-X 2 1-XX

Pitch: _____

1 = 2.54mm PGA Adapter

Number of Position:-

068 = 68 PIN 121 = 121 PIN

306 = 306 PIN

PGA Basic Body Size:

$$9 = 9 \times 9 \qquad 0 = 10 \times 10$$
$$A = 11 \times 11$$

Pin Size:

Contact Plated:

0 = Tin 200u"

1 = Gold Flash

2 = Gold 2u
3 = Gold 15u








4 = Gold 30u"

5 = Gold 3u"

Insulator Material:

[illegible]

PGA Footprint



PGA basic body 11X11 PGA basic body 13X13 PGA basic body 13X13






Number of contacts: 68 Number of contacts: 84 Number of contacts: 121

PGA basic body 14X14 PGA basic body 15X15

Number of contacts: 132 Number of contacts: 145

PGA basic body 16X16 PGA basic body 17X17

Number of contacts: 156 Number of contacts: 169



PGA basic body 17X17 PGA basic body 18X18

Number of contacts: 241 Number of contacts: 225

PGA basic body 19X19 PGA basic body 19X19

Number of contacts: 238 Number of contacts: 306

PGA basic body 20X20 PGA basic body 20X20

Number of contacts: 400 Number of contacts: 400

E		Units	mm	Scale	≥1:1	Drawing By	Date	leycomm Http://www.leycomm.com		深圳市联益康电子有限公司 TEL: +86 (755) 26078616 FAX: 26070522	
D		Tolerance Unless Otherwise Specified				Vance	2004/07/12				
C						Reviewed By	Date	Date	2004/07/12	Title	PGA Adapter (PGA Footprint)
B						Sandy	2004/07/12	Sheet	2 of 2		
A						Approval By	Date	Thirt Angle Projection		Drawing No.	REV
REV						ECN.NO.	Date	Angle	~ ± 3°		A